



**EUROPEAN PATENT APPLICATION**

(21) Application number: 89312533.6

(51) Int. Cl.<sup>5</sup>: H03K 17/08, H03K 17/22

(22) Date of filing: 30.11.89

(30) Priority: 02.12.88 JP 306633/88  
24.12.88 JP 327067/88  
21.09.89 JP 247473/89

(43) Date of publication of application:  
13.06.90 Bulletin 90/24

(84) Designated Contracting States:  
DE FR GB

(88) Date of deferred publication of the search report:  
27.03.91 Bulletin 91/13

(71) Applicant: MITSUBISHI DENKI KABUSHIKI  
KAISHA  
2-3, Marunouchi 2-chome Chiyoda-ku  
Tokyo(JP)

(72) Inventor: Suda, Shinji c/o Mitsubishi Denki  
K.K.


Kitaitami Selsakusho 1 Mizuhara 4-chome  
Itami-shi Hyogo-ken(JP)  
Inventor: Kobayashi, Hiroshi c/o Mitsubishi  
Denki K.K.  
Kitaitami Selsakusho 1 Mizuhara 4-chome  
Itami-shi Hyogo-ken(JP)  
Inventor: Hongo, Katsunobu c/o Mitsubishi  
Denki K.K.  
Kitaitami Selsakusho 1 Mizuhara 4-chome  
Itami-shi Hyogo-ken(JP)  
Inventor: Nakao, Hiroyuki c/o Mitsubishi Denki  
K.K.  
Kitaitami Seisakusho 1 Mizuhara 4-chome  
Itami-shi Hyogo-ken(JP)

(74) Representative: Beresford, Keith Denis Lewis  
et al  
BERESFORD & Co. 2-5 Warwick Court High  
Holborn  
London WC1R 5DJ(GB)

(54) Complementary circuit device returnable to normal operation from latch-up phenomenon.

(57) A complementary circuit device which cancels a latch-up phenomenon to return to normal operation includes a complementary circuit (52), a latch-up detection circuit (54) and a reset circuit (84). The complementary circuit (52), which is normally started from a prescribed state in response to initial power supply, may be erroneously started when the same is resupplied with power immediately after occurrence of a latch-up phenomenon. The latch-up detection circuit (54) detects a latch-up phenomenon occurring in the complementary circuit (52). The reset circuit resets the complementary circuit (52) from the prescribed state in response to an output from the latch-up detection circuit (54). The complementary circuit (52) is reset from the prescribed state similarly to the case of initial power supply, whereby the same is normally started to return to its operation also upon cancellation of the latch-up phenomenon.

FIG. 8





European  
Patent Office

## EUROPEAN SEARCH REPORT

Application Number

EP 89 31 2533

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
X	DD-A-2 605 93 (VEB FORSCHUNGSZENTRUM) * Whole document *	1	H 03 K 17/08 H 03 K 17/22
Y	---	2-18	
Y	GB-B-2 120 427 (NISSAN MOTOR CO., LTD) * Page 3, line 20 - page 4b, line 17 *	2-18	
A	US-A-4 594 633 (TOWNSEND et al.) ---		
D,A	PATENT ABSTRACTS OF JAPAN, vol. 9, no. 65 (E-304), 26th March 1985; & JP-A-59 202 659 (TOSHIBA K.K.) 16-11-1984 -----		
			TECHNICAL FIELDS SEARCHED (Int. Cl.5)
			H 03 K H 02 H G 06 F
The present search report has been drawn up for all claims			
Place of search		Date of completion of search	Examiner
The Hague		27 December 90	SEGAERT P.A.O.M.P.
<b>CATEGORY OF CITED DOCUMENTS</b>			
X: particularly relevant if taken alone			
Y: particularly relevant if combined with another document of the same category			
A: technological background			
O: non-written disclosure			
P: intermediate document			
T: theory or principle underlying the invention			
E: earlier patent document, but published on, or after the filing date			
D: document cited in the application			
L: document cited for other reasons			
&: member of the same patent family, corresponding document			